

Burglar and fire-proof safes

Series HTFIII 320

Security grade Euro VdS class III burglar-proof according to EN 1143-1

Grade S 60 P fire-proof according to EN 1047-1

■ Construction

- Total door thickness: 137 mm
- Body and door are all-side multi-walled
- 3-side lockable bolt work with waler bolts, and an additional end-to-end rear profile which engages on the hinge side
- Bore-proof armour plate in the lock area
- Floor anchorage mechanism

■ Standard fittings

- Single-door: right hinged DIN
- Door aperture angle 180°
- Height adjustable shelves (see table)
- Light grey lacquer RAL 7035

■ Locking mechanism

- Double-bit lock (including 2 keys)

■ Insurance cover

Resistance grade VdS III

€ 100.000,-*/** commercial

€ 200.000,-*/** private

**Fire protection
for 60 minutes**

HTFIII 320-04

Burglar and fire-proof safes



Series HTFIII 320	Ext. dimensions H x W x D (in mm)	Int. dimensions H x W x D (in mm)	Weight (in kg)	Volume (in litre)	No. of shelves	No. of doors
HTFIII 320-01	776 x 591 x 660	530 x 363 x 295	631	57	2	1
HTFIII 320-02	936 x 591 x 660	690 x 363 x 295	770	74	2	1
HTFIII 320-03	1298 x 832 x 704	1052 x 604 x 340	1340	216	2	1
HTFIII 320-04	1483 x 832 x 704	1237 x 604 x 340	1485	254	3	1
HTFIII 320-05	1668 x 832 x 704	1422 x 604 x 340	1640	292	3	1